

Element

UUR

KENDA

SHIMANO

SR SUNTOUR



PARTS

SPECIFICATION

FRAME	ELEMENT 036 27.5" T44 D55, 15.5", H/T 100mm D/T 57X1.8T, 44X1.8T, 57X1.8, 22X1.6T
FORK	ELEMNT ALLOY SHOULDER ALLOY LEGS 27.5" AIR SUSPENSION REMOTE LOCKOUT 28.6*170mm, ED32mm, 38mm, PITCH100mm
HEADSET	ELEMENT D13 44X55X28.6X15HX25H
ALLOY WASHER	FEIMIN 28.6X5mm
HANDLEBAR	UUR HB-105BT 31.8X22.2X2.0TX760mm
STEM	UUR AS-261C 60mmX28.6X31.8
SEATPOST	UUR SP-609 30.4X350MM
SEATPIN	UUR YX-049 34.9mm BK WITH QR
GRIPS	JD-201 TPR 22.2X130mm
BB SHEEL	N/A
CHAINWHEEL	CHARM-34T ALLOY LEGS 32TX170mm
CHAIN	PYC P12 INDEX 12S 1/2 3/32 L118
PEDAL	ELEMENT FP-922 9/16
BRAKE LEVER	N/A
FRONT BRAKE	SHIMANO MT200 HYDRAULIC LEFT FOR FRONT F: 800mm
REAR BRAKE	SHIMANO MT200 HYDRAULIC RIGHT FOR RIGHT R: 1500mm
ROTOR	160mmX2PCS
RIMS	HL-28D 27.5X1.75X32HX14GXH20mm A/V
SPOKES	45# 14G 64PCS F/R:285/287mm
TIRE	KENDA K1127A 29X2.20 60TPI
INNER TUBE	KENDA AV 29X1.95/2.10 AV:33mm
TAPE	NYLON 29X20
FREEWHEEL	CASSTTE INDEX 12PCS 12S 11-50T
FRONT HUB	WZ-282 F:3/8X32HX100X112mm with QR
REAR HUB	WZ-282 R:3/8X32HX135X152mm with QR
LEFT SHIFT LEVER	N/A
RIGHT SHIFT LEVER	SHIMANO SL-M6100 12S
FRONT DER.	N/A
REAR DER.	SHIMANO RD-M6100 12S
SHIFT CABLE	SP R:1300mm+220mm
WATER BOTTLE BOLTS	M5X15mm 2PCS
REFLECTOR	H85 H05 H86
TOOLS	Included



Element



All measurements provided in cm unless otherwise noted.

Frame size number	15.5	17.5
Frame size letter	S	M
Wheel size	27.5"	29"
A – Seat tube	36.8	41.9
Effective seat tube angle	73.5°	73.0°
C – Head tube length	9.0	9.0
D – Head angle	69.3°	69.5°
E – Effective top tube	55.5	60.2
F – Bottom bracket height	30.2	31.0
G – Bottom bracket drop	4.8	5.8
H – Chainstay length	43.8	43.8
I – Offset	4.2	4.2
J – Trail	8.8	9.3
K – Wheelbase	106.6	110.0
L – Standover	68.6	74.8
M – Frame reach	38.5	41.8
N – Frame stack	57.4	60.2

